CLIENT Project (AFE) No:	~~ F → O : t → L 1 O A	Job No.:	8122
CLIENT DOC No.	Ensite USA	Doc No.:	
	E110110 00/1	Revision:	В
		Rev. Date:	5/16/2025
	KYMEA METER STATION		

KYMEA METER STATION DATA SHEET - METER SKID

	APPROVALS	
☐ ISSUE FOR REVIEW		
☐ DRAFT ISSUE FOR COMMENTS	Mechanical Engineer	Date
■ ISSUE FOR BID □ ISSUE FOR CLIENT APPROVAL	Andrew Roach	5/16/2025
☐ ISSUE FOR CONSTRUCTION – Rev 0	Project Manager	Date
☐ ISSUE AS REVISED DOCUMENT	Byron Marlowe	3/3/2025
	Client - Project Manager	Date

Approvals:						
	By:	Date:	1			
Initiator	СВ	03/03/25				
Process	N/A					
Mechanical	CB	03/03/25	Revisions:			
Civil	N/A		Rev.:	Date:	By:	Approval:
Electrical	DD	03/03/25	Α	03/03/25	CB	IFR
Instrumentation	НО	03/03/25	В	05/16/25	AR	IFB
Project Eng.	AR	05/16/25				
Project Mgr.	BM	03/03/25				
Client					<u> </u>	

Reference Documents

Design Standard: Meter Station, EC-DS-007, Revision 1, 04/10/2019
OP-CC-GS-COAT-001 General Coating Specifications, Revision 3.20, 05/31/2024
EnSiteUSA P&ID

This document is solely for the use of the contractual Company and vendors of EnSiteUSA. EnSiteUSA assumes no liability to any other party for any representations contained in this document.





REV.	STATUS	DATE	BY	CHK.	APPR.	ISSUE DATE		8122	
A	For Review	3/3/2025	СВ	JS	BM	3/4/2025	CLIENT:	BWP / Texas Gas	
	1				1		PROJECT:	KYMEA	
	-						LOCATION: DOC. NO.:	Madisonville, KY	
			l				PROJECT ENGI	NEER: Chris Baca	
							- NOJECI ENGI	CIIII3 Data	
					GENER	AL INFORMATION			
	X	Proposal		Purchase		As Built		complete Data Sheet with information not	
Applicable To:	KYMEA						otherwise prov	vided by KYMEA.	
For:		Delivery to KYN	MEA Facility		_	Equipment No.'s	4		
Site: Description:	Madisonville,	/ dual 100% run			_	No. Required: Vendor:	1 TBD		
Application:	Custody Trans		15		_	Reference Drawing No.			
Point of		VP of Market A	nalystics		_	Ship To	KYMEA Energy	Center I	
Procurement:	rleesman@ky		,			•	Attn: Stan Con		
		icipal Energy A	gency (KYMEA)				1957 AC Slator	ın Rd.	
	1700 Eastpoin	t Parkway Ste. 2	220				Madisonville, I	KY 42431	
	Louisville, KY	10223							
					AMBI	ENT CONDITIONS			
Maximum Ambi			110			Earthquake Zone		SDC D	
Minimum Ambie	ent Temperatur	е	-20	· · ·		Maximum Wind Velocit	CY .	120_mph	
					PROC	ESS CONDITIONS			
Minimum Gas Te	emperature		-4	°F	. 1.00	Meter Type		(2) Ultrasonic	
Maximum Gas T			158			Flow Direction		Single Direction	
Minimum Gas Pi			0	PSIG		Maximum Differential P	Pressure	N/A psid flange to flange	
Maximum Gas P				PSIG		Design Pressure		965 PSIG	
Minimum Gas Fl				SCFH		Design Flowrate		26949 lbm/hr	
Maximum Gas F				lbm/hr		Gas Specific Gravity		0.6	
Maximum Noise	: dl 31[85	dB					
					EQU	JIPMENT DATA			
						RIFICE METER			
Plate Diameter				IA.	_in.	Diff Pressure Connectio	n Location	NA NA	
Plate Thickness Plate Material				IA IA	_in.	Flow Conditioner Length of Pipe Upstrear	m	NA NA	
Allowable Beta F	Ratio Range			IA IA	_	Length of Pipe Downstr		NA NA	
RMS Finish	natio nange			IA	_	Pipe WT	cum	NA NA	
Pipe Grade				IA	_	%SMYS at MWP		NA NA	
Required Accura	асу			IA	- -	Weather Protection		NA	
Equipment Mou				IA	_	Type of Orifice Meter		NA	
				IA	P/	OTARY METER			
Meter Output			N	IA	, ni	Required Accuracy		NA	
Actual Flow Ran	ge			IA .	_	%SMYS at MWP		NA NA	
Internal Materia	-			IA	_	Paint Coating		NA	
Temperature Co		n		IA	_	Flange Size and Rating		NA	
Pressure Correct	tion Location		N	IA	_				
					ULTI	ASONIC METER			
Minimum Allow	able Velocity		2		ft/s	Type of Temp/Pressure	XMTR	Individual	
Maximum Allow	able Velocity		80		ft/s	Flow Conditioner		Required	
Number of Passe			Multi-path		_	Length of Pipe Upstrear			
Number of Trans			2		_	Length of Pipe Downstr	eam	0.2001	
Transducer Mou	unting Method		Direct Insertio	n	-	Pipe WT		0.280"	
Pipe Grade			ASTM A106 Gr	R Minimum		%SMYS at MWP Weather Protection		19.3 Required	
Required Accura	acv		0.35%	ıvınınınuill ت	_	Local Readout		Yes	
Equipment Mou			Skid		-	Paint Coating		BWP OP-CC-GS-COAT-001	
			-						
					TU	RBINE METER			
Meter Output			N	IA	_	Required Accuracy		NA	
Actual Flow Ran	ge			IA	_	%SMYS at MWP		NA	
Internal Materia				IA	_	Paint Coating		NA	
Temperature Co		n		IA.	_	Flange Size and Rating		NA NA	
Pressure Correct	tion Location			IA	_	Flow Conditioner		NA NA	
					AN	NUBAR METER			
Meter Output			N	IA		Required Accuracy		NA	
Actual Flow Ran	ge			IA	_	%SMYS at MWP		NA	
Internal Materia				IA	_	Paint Coating		NA	
Temperature Co		n		IA.	_	Flange Size and Rating		NA NA	
Pressure Correct				IA IA	-	Flow Conditioner		NA NA	
Length of Pipe U Length of Pipe D				IA IA	-	Required Accuracy		NA NA	
	di caiii		'						
Meter Outsut				IA	co	RIOLIS METER		NA	
Meter Output Actual Flow Ran	ge			IA IA	_	Required Accuracy %SMYS at MWP		NA NA	
Internal Materia				IA IA	_	Paint Coating		NA NA	
Temperature Co		on		IA	_	Flange Size and Rating		NA NA	
Pressure Correct				IA	_	Flow Conditioner		NA NA	
Length of Pipe U				IA	_	Required Accuracy		NA NA	
Length of Pipe D	ength of Pipe Downstream NA Pipe Grade NA								
								NA	